



LM-I Series Laser Distance Meters

LM60-I/LM80-I/LM100-I/LM120-I/LM150-I



Measurement units: m/ft/in/in+ft



| SPECIFICATIONS | LM60-I | LM80-I | LM100-I | LM120-I | LM150-I |
|--------------------------|-------------------------------|--------|---------|---------|---------|
| Display type | EBTN | LCD | | | |
| Display size | | | | | |
| Range | 60m | 80m | 100m | 120m | 150m |
| Min. display unit | 0.001m | | | | |
| Measurement units | m/ft/in | | | | |
| Measurement basis | front/rear | | | | |
| Accuracy | ±(2mm+5 x 10 ⁻⁵ D) | | | | |
| Laser class | 2 | | | | |
| Laser type | 630~670nm, <1mW | | | | |
| Features | | | | | |
| Single measurement | √ | | | | |
| Continuous measurement | √ | | | | |
| Max/Min/Area | √ | | | | |
| Volume | √ | | | | |
| Pythagoras | √ | | | | |
| Add/Subtract | √ | | | | |
| Auto leveling horizontal | — | | √ | | |
| Auto leveling vertical | — | | √ | | |
| Data storage | 20 groups | | | | |
| Auto power off | 3 minutes without operation | | | | |
| Auto laser off | 30s without operation | | | | |
| Auto backlight off | 10s without operation | | | | |
| Tilt angle | — | | ±90.0° | | |
| Audio indication | √ | | | | |
| Battery status display | √ | | | | |
| Storage temperature | -20°C~70°C | | | | |
| Operating temperature | 0°C~40°C | | | | |

